

# SUNMI M2 MAX Smart Mobile Terminal

A rugged tablet built to improve your store operations.

## Rugged

Featuring IP65 and 1m drop, M2 MAX can stand up to challenges in working environments; The Corning Gorilla Glass used in its 10.1" HD screen is more resistant to scratches and abrasions during use.

## Smooth Operations

Equipped with a high-performance octa-core processor and large memory, it can run multiple tasks smoothly.

## Long Run Time

With a built-in 8360mAh battery, it can work 12 hours continuously or stand by for 20 days.

## Highly Flexible

Optional accessories for M2 MAX include hand strap and cradle, only to meet your needs in more business scenarios.



\*Scanner Version: The scanner is non-removable.



## SUNMI M2 MAX Tech Specs

<b>Product Model</b> Config 1: TF700 (Wi-Fi Ver.) Config 2: TF701 (4G Ver.)	<b>OS</b> SUNMI OS (*based on Android 9.0)	<b>Processor</b> Kryo-260 octa-core, 2.2GHz	<b>Memory</b> Config 1: 3GB RAM + 32GB ROM Config 2: 4GB RAM + 64GB ROM	<b>Display</b> 10.1" FHD, 1920*1200 Capacitive multi-touch
<b>Camera</b> Front: 5MP FF Rear: 13MP, Flash, AF 1D/2D barcode reading	<b>NFC Reader</b> Type A & B card, Mifare card FeliCa card. ISO/IEC 14443, ISO15693 standards compliant	<b>Speaker</b> 2* 1W	<b>PSAM Card Slot</b> 1* PSAM	<b>vSIM</b> Supports vSIM (Config 2)
<b>SIM Card Slot</b> 1*MicroSD (TF) (Config 1) 2* NANO SIM OR 1* NANO SIM+1* MicroSD (TF) (Config 2)	<b>Network</b> 2G & 3G & 4G	<b>Wi-Fi</b> 2.4GHz/5GHz IEEE 802.11a/b/g/n/ac	<b>Bluetooth</b> Bluetooth 5.0 BLE	
<b>GPS</b> AGPS GPS/Glonass/Beidou (Config 2)	<b>Sensors</b> Gravity sensor, light sensor, compass sensor, hall sensor.	<b>Buttons</b> 1* Power on/off button (lock screen button) 2* Volume (+/-) button	<b>MIC</b> 2* MIC	<b>Ports</b> 1* Type-C, OTG supported 1* Audio Jack, supports POGO Pin
<b>Battery</b> Nonremovable LiPo battery 3.85V/8360mAh	<b>Power Adapter</b> Input: AC 100~240V Output: DC 5V/2A	<b>Dimensions (L*W*H)</b> 245.6*164.4*9.9mm (thinnest)	<b>Weight</b> Standard Version: 673g Scanner Version: 735g	<b>Protection Ratings</b> IP65 1.0m drop spec *Data from SUNMI Lab.
<b>Environment</b> Operating temp.: -20°C~55°C Storage temp.: -40°C ~ 70°C	<b>Accessories</b> hand strap charging and extendable cradle (optional) protective case (optional)	<b>Scanner</b> Professional 2D scan engine (*Only supported by scanner version)		